Hydraulic Vertical Baler

185

... for general purpose – variable, economical and powerful





Compaction force 6 t Bale weight 40-60 kg



Compaction force 8,5 t Bale weight 50-80 kg



Compaction force 25-30 t Bale weight 250-360 kg





18 S

The successor of the well established DIXI 16 S which operates on many thousands of locations, is now available with a compaction force of 18 t and has an electronically controlled operating comfort: Switching of programming for the compaction of "paper/cardboard" or "foil" and variable bale size.

- Micro processor control without limit switch. Low maintenance design. Well arranged LCD display.
- Automatic start when closing the feed flap rapid compaction cycle, automatic ram return.
- Adjustable compaction time: The material can be kept under pressure.
- Easy tying of the bales and hydraulic, complete ejection.
- Two-phase hydraulic unit of the control block guarantees a rapid compaction cycle.
- Generously designed hydraulics: High compaction force with low hydraulic pressure and low drive performance

Model DIXI		18 S
Motor	kW	4
Voltage	V/Hz	400/50
Compaction force		
r	nax. t	18
Cycle time	s	22
Compaction time	s	12
Opening		
wxh	cm	107 x 62
Height from floor	cm	98
Bale size*		
w x h x d approx.	cm	110 x 70 x 70-80
Bale weight**	kg	120 - 180
Overall width	cm	152
Overall depth	cm	95
Overall height	cm	197
Gross weight	kg	850










Special equipment:

- Connection for dust extraction
- Explosion proof version





^{**}depending upon kind of material Technical details and colours subject to chance without prior notice. (1.04)





Robust: The twofold guided press ram



Low maintenance: the micro processor



Easy to operate: The ejector



Baling systems for the volume reduction of recyclable material